

TO-92 Encapsulate Three-terminal Voltage Regulator

CJ78L05 Three-terminal positive voltage regulator

FEATURES

Maximum Output Current I_O : 0.1 A

Output Voltage V_O : 5 V

Continuous Total Dissipation


P_D : 0.625W ($T_a=25^\circ\text{C}$)

TO-92

1. OUT

2. GND

3. IN




ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_I	30	V
Operating Junction Temperature Range	T_{OPR}	-25~+125	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55~+150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JUNCTION TEMPERATURE ($V_I=10\text{V}$, $I_O=40\text{mA}$, $C_i=0.33\mu\text{F}$, $C_o=0.1\mu\text{F}$, unless otherwise specified)








Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Output voltage	V_O		25 $^\circ\text{C}$	4.8	5.0	5.2	V
		7V $\leq V_I \leq 20\text{V}$, $I_O=1\text{mA} \sim 40\text{mA}$	0-125 $^\circ\text{C}$	4.75	5.0	5.25	V
		$I_O=1\text{mA} \sim 70\text{mA}$		4.75	5.0	5.25	V
Load Regulation	ΔV_O	$I_O=1\text{mA} \sim 100\text{mA}$	25 $^\circ\text{C}$		15	60	mV
		$I_O=1\text{mA} \sim 40\text{mA}$	25 $^\circ\text{C}$		8	30	mV
Line regulation	ΔV_O	7V $\leq V_I \leq 20\text{V}$			32	150	mV
		8V $\leq V_I \leq 20\text{V}$	25 $^\circ\text{C}$		26	100	mV
Quiescent Current	I_q		25 $^\circ\text{C}$		3.8	6	mA
Quiescent Current Change	ΔI_q	8V $\leq V_I \leq 20\text{V}$	0-125 $^\circ\text{C}$			1.5	mA
	ΔI_q	1mA $\leq V_I \leq 40\text{mA}$	0-125 $^\circ\text{C}$			0.1	mA
Output Noise Voltage	V_N	10Hz $\leq f \leq 100\text{KHz}$	25 $^\circ\text{C}$		42		μV
Ripple Rejection	RR	8V $\leq V_I \leq 20\text{V}$, $f=120\text{Hz}$	0-125 $^\circ\text{C}$	41	49		dB
Dropout Voltage	V_d		25 $^\circ\text{C}$		1.7		V

TYPICAL APPLICATION





Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

Typical Characteristics




TO-92 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.400	4.700	0.173	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015

TO-92 Suggested Pad Layout




- Note:
1. Controlling dimension: in millimeters.
 2. General tolerance: $\pm 0.05\text{mm}$.
 3. The pad layout is for reference purposes only.

NOTICE


JCET reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

TO-92 PACKAGE TAPEING DIMENSION



Dimiensions are in millimeter

A1	A	T	P	P0	P2	F1	F2	W
4.5±0.2	4.5±0.2	3.5±0.2	12.7±0.3	12.7±0.2	6.35±0.3	2.5±0.3	2.5±0.3	18.0+1.0/-0.5
W0	W1	W2	H	H0	D0	t1	t2	ΔP
6.0±0.5	9.0±0.5	1.0 MAX.	19.0±1.0	16.0±0.5	4.0±0.5	0.4±0.05	0.2±0.05	0 ± 1.0



Package	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92	2000 pcs	333×162×43	20,000 pcs	350×340×250